

Specification

Specification		
Model		TH-MSLT-400Y-1
Output voltage	V	DC24V
Power of lamp	W	4*100W (LED,120lumens per watt)
Mast Height	М	7
Telescoping Mast	By Aluminum, be round	4 stages lift mast, Mechanical,360° rotation
Range of exposures	М	180
Working time	Hour	12
Charging time	Hour	10
Tail light	V	12V, LTL0801ARW, Australia standard
Tow	KG	2000KG,CO2000Z,Australia standard
Charge controller	A	30A,24V, MPPT solar controller
Winch	LB	Hand winch, 2500LBS
Tire diameter	mm	690mm, ST215/70R15C
Battery power	АН	4*120AH/12V
Dimensions	length×width×height	2650×1500×1950 mm
weight	complete appliance	950kg
Solar Panel	W	2*300W Monocrystalline
Packing	Wooden Box,5 sets/40ft container	
Warranty/Life	1.Whole system :2 years warranty 2.Solar panel: 10 years warranty/25 years life 3.LED light: 2 years warranty/50,000 hours life span	

The advantage/improvement of ours:

- 1. Fine design, easy installation and operation.
- 2. Thicker steel plate structure, durable quality, much safer during towing.

- 3. Aluminum telescoping round mast, better appearance, higher strength.
- 4. Full fuse protected, easy & safe fro common people to operate.
- 5. Monocrystalline silicon solar panel, higher conversion efficiency.
- 6.Deep cycle gel battery,longer shelf life.Low voltage protection and overcharging protection.
- 7.SUV Type Tire, better for traction under the harsh condition like sand and mountain area.
- 8.Brake and Tail light can give more guarantee on the road traction.
- 9. More clearance are given during selection of electrical components to protect the whole system.
- 10.To ensure the strength of the trailer, we have used more square steels instead of welded steels.

Note: We can design and fabricate according to your specific requirements.

Commercial Condition

Payment Terms:50% TT in advance,the balance paid before shipment Lead Time:35 days after Deposit Validity for this quotation:20 days

